

Product Data Sheet

TARMAC WALL & FLOOR GROUT

TILING

Description

Tarmac Wall & Floor Grout is a cement based anti-fungal powdered grout. It is available in a range of colours and when mixed with water, produces a creamy and easily worked mortar with good filling properties, enabling deep joints to be filled in one operation.

Uses

Tarmac Wall & Floor Grout can be used in the following applications:

- For grouting wall and floor tiles with joints between 2mm and 18mm.
- Can be used in power showers, bathrooms and kitchens.
- Suitable for use over timber surfaces.
- For internal and external application.
- Suitable for use over underfloor heating.
- For use with glazed ceramic wall tiles, mosaics and natural stone tiles.

Special Properties

- Anti-fungal.
- Available in a range of colours.
- Easy to use and clean.
- Water and frost resistant.
- Flexible.

Typical Performance

Technical Data (Tested at 20°C)	
Joint Width	2 – 18mm
Open Time	45 minutes
Set Time	24 hours
Colours	White, Grey, Buff and Anthracite

Coverage

Coverage is dependent on the size of the tiles being laid. The calculation below can be used to estimate the amount of grout required

Add: length and breadth of tile together

Multiply: result by joint width

Multiply: result by joint depth

Multiply: result by 1.6

Divide: result by length of tile

Divide: result by breadth of tile

The result is the material requirement in kg/m²

Preparation

All tiles must be firmly fixed and the joints must be clean and sound and free of excess adhesive and bedding mortar.

Mixing

Add 5kg of **Tarmac Wall and Floor Grout** to 1.2 litres of cold clean water in a clean container whilst mixing. Mix with a drill and suitable mixing attachment for 2 minutes until a slump free creamy mortar is produced. Allow to stand for 2 minutes and then remix. Mix only sufficient material to be used in the working time and do not remix or rewet.

Application

Using a rubber squeegee or rubber backed trowel work the mixed grout thoroughly into the joints ensuring they are completely filled. Excess grout should be removed as work proceeds and any residues left on the tile face can be removed by wiping off with a damp sponge between 15 minutes and 2 hours after application. Any dry film remaining on the tile surface can easily be removed by polishing off with a dry cloth when the grout has hardened in the joints..

Do not apply in temperatures below 5°C or above 25°C. Frost free conditions are required during curing.

Remove grout from tools in water as soon as possible after use.

Quality Control

All Pozament products are factory blended, tested and packaged to quality control procedures in accordance with BS EN ISO 9001.

Clean up and Spillages

Dry powders should be swept up and disposed of in accordance with the Local Authority.

Packaging and Storage

Tarmac Wall & Floor Grout is available in nominally 5kg sacks, palletised and shrink-wrapped.

Tarmac Wall & Floor Grout should be stored in cool dry areas clear of the ground, sheeted or under cover and stacked not more than two pallets high.

The product should be used on a first in – first out basis.

Shelf life is minimum 6 months but could be in excess of 9 months subject to temperature and humidity.

Information, prices & ordering

For technical information, pricing and to place orders contact our Sales Office on the following:

Telephone: **08444 630046** Fax: **08443 099703**

Email: pozament@tarmac.co.uk

Visit our website: www.pozament.co.uk

Pozament - Tarmac Building Products Ltd.,
Swains Park Industrial Estate, Park Road,
Overseal, Swadlincote, Derbyshire DE12 6JT.

Health & Safety

Health and safety advice, which must be followed, can be found on the Material Safety Data Sheet. Users are advised to wear face mask, goggles, gloves and overalls when handling, mixing and applying cementitious products.

Contains Portland Cement. Contains Chromium (VI), which may produce an allergic reaction. Clothing contaminated by wet cement should be removed immediately and washed before reuse. R38 - Irritating to skin. R41 - Risk of serious damage to eyes. S26 - In case of contact with eyes, rinse immediately with water and seek medical advice. S37/39 - Wear suitable gloves and eye/face protection. S2 - Keep out of reach of children